



3.5 HARD DRIVE DATA SHEET

Smart. Safe. Secure. Video Optimised and Edge Ready

Seagate[®] SkyHawk[™] AI 20 TB is a video-optimised drive designed for NVRs with artificial intelligence (AI) for edge applications.





Best-Fit Applications

- Network video recorders (NVR)
- Al-enabled NVR systems



Key Advantages

ImagePerfect[™] Al firmware delivers zero dropped frames while supporting heavier workloads.

Versatile capabilities intelligently adapt to the scale of your AI environment, supporting up to 64 HD video streams and 32 AI streams.

SkyHawk Health Management actively helps protect your video storage by focusing on prevention, intervention and recovery options.¹ Included RAID RapidRebuild™ provides 3× faster volume rebuilds.


Class-Leading Reliability and Dependability SkyHawk Al drives are rated for 2M hours MTBF and a 550 TB/year workload rate for more than 3x that of standard surveillance hard drives. Backed by a 5-year limited warranty.

Powerful processing to welcome workload challenges — SkyHawk Al supports video analysis and recording simultaneously with GPU analytics workloads.

Enjoy consistent performance with built-in rotational vibration sensors providing reliable storage for NVR with little lag or downtime.

Multi-bay support helps you meet your growing storage demands with up to 16+ bays.

¹ Contact your Seagate sales representative for further information





Specifications	20 TB	18 TB	16 TB	12 TB	10 TB
Capacity	20TB	18TB	16TB	12TB	10TB
Standard Model Numbers	ST20000VE000	ST18000VE000	ST16000VE000	ST12000VE0008	ST10000VE0008
Interface	SATA 6 Gb/s				
Recording Technology	CMR	CMR	CMR	CMR	CMR
Drive Design	Helium	Helium	Helium	Helium	Helium
Features and Performance					
Drive Bays Supported	16+	16+	16+	16+	16+
Al Channels	32	32	32	32	32
Al Real Time Capture Events/Sec ^{1,2}	Up to 120				
Al Real Time Compare Events/Sec ^{1,2}	Up to 96				
HD Cameras Supported ³	Up to 64				
RV Sensors	Yes	Yes	Yes	Yes	Yes
Max. Sustained Transfer Rate OD (MB/s)	260MB/s	260MB/s	250MB/s	250MB/s	250MB/s
Cache (MB)	256	256	256	256	256
Reliability/Data Integrity					
Tarnish Resistant	Yes	Yes	Yes	Yes	Yes
Load/Unload Cycles	600,000	600,000	600,000	600,000	600,000
Non-recoverable Read Errors Rate, Max	1 per 10E15				
Power-On Hours per year	8,760	8,760	8,760	8,760	8,760
Workload Rate Limit (WRL) ⁴	550	550	550	550	550
Mean Time Between Failures (MTBF) (hours)	2,000,000 hr				
Warranty, Limited (years) ⁵	5	5	5	5	5
Power Management					
Startup Current, Typical (12V, A)	2	2	2	2	1.8
Average Operating Power (W)	7.72 W	7.7 W	6.7 W	6.7 W	6.9 W
Idling Average (W)	3.5 W	3.5 W	5.1 W	5.1 W	4.9 W
Standby Mode/Sleep Mode, Typical (W)	1/1	1/1	1.05/1.05	1.05/1.05	1.2/1.2
Voltage Tolerance (5 V)	±5%	±5%	±5%	±5%	±5%
Voltage Tolerance (12 V)	±10%	±10%	±10%	±10%	±10%
Environmental/Temperature					
Operating (Ambient, min °C)	0	0	0	0	0
Operating (drive reported, max °C) ⁶	65	65	65	65	65
Non-operating (ambient, min °C)	-40	-40	-40	-40	-40
Physical					
Height (mm/in, max)	26.11 mm/1.028 in				
Width (mm/in, max)	101.85 mm/4.01 in				
Depth (mm/in, max)	146.99 mm/5.787 in				
Weight (g/lb, typical)	680 g/1.499 lb	670 g/1.477 lb	670 g/1.477 lb	670 g/1.477 lb	690 g/1.521 lb
Carton Unit Quantity	20	20	20	20	20
Cartons per Pallet/Cartons per Layer	40/8	40/8	40/8	40/8	40/8

¹ Events can be human, vehicle, or object capture.

² Tested and verified using embedded AI NVR – 64-ch HD recording, 16-ch PB. Average picture size \sim 250 KB

^{3 1080}P, H.265, 25 fps

⁴ SkyHawk Al surveillance drives are designed for always-on workloads of 550 TB/year. For higher transaction workloads, see Seagate's enterprise-class drive offerings.

 $^{{\}tt 5~Extended~warranty~options~available.~Consult~your~distributor~for~details.}$

⁶ Seagate does not recommend operating at sustained extreme temperatures. Operating at higher temperatures will reduce useful life of the product.





Specifications	10 TB	8 TB	
Capacity	10TB	8TB	
Standard Model Numbers	ST10000VE000	ST8000VE000	
Interface	SATA 6 Gb/s	SATA 6 Gb/s	
Recording Technology	CMR	CMR	
Drive Design	Air	Air	
Features and Performance			
Drive Bays Supported	16+	16+	
Al Channels	32	32	
Al Real Time Capture Events/Sec ^{1,2}	Up to 120	Up to 120	
Al Real Time Compare Events/Sec ^{1,2}	Up to 96	Up to 96	
HD Cameras Supported ³	Up to 64	Up to 64	
RV Sensors	Yes	Yes	
Max. Sustained Transfer Rate OD (MB/s)	245MB/s	250MB/s	
Cache (MB)	256	256	
Reliability/Data Integrity			
Tarnish Resistant	Yes	Yes	
Load/Unload Cycles	600,000	300,000	
Non-recoverable Read Errors Rate, Max	1 per 10E15	1 per 10E15	
Power-On Hours per year	8,760	8,760	
Workload Rate Limit (WRL) ⁴	550	550	
Mean Time Between Failures (MTBF) (hours)	2,000,000 hr	1,500,000 hr	
Warranty, Limited (years) ⁵	5	5	
Power Management			
Startup Current, Typical (12V, A)	2	2	
Average Operating Power (W)	10.1 W	7.92 W	
Idling Average (W)	7.8 W	7.26 W	
Standby Mode/Sleep Mode, Typical (W)	1/1	0.96/0.96	
Voltage Tolerance (5 V)	±5%	±5%	
Voltage Tolerance (12 V)	±10%	±10%	
Environmental/Temperature			
Operating (Ambient, min °C)	0	0	
Operating (drive reported, max °C) ⁶	65	65	
Non-operating (ambient, min °C)	-40	-40	
Physical			
Height (mm/in, max)	26.11 mm/1.028 in	26.11 mm/1.028 in	
Width (mm/in, max)	101.85 mm/4.01 in	101.85 mm/4.01 in	
Depth (mm/in, max)	146.99 mm/5.787 in	146.99 mm/5.787 in	
Weight (g/lb, typical)	720 g/1.587 lb	715 g/1.579 lb	
Carton Unit Quantity	20 20		
Cartons per Pallet/Cartons per Layer	40/8	40/8	

¹ Events can be human, vehicle, or object capture.

- 2 Tested and verified using embedded AI NVR 64-ch HD recording, 16-ch PB. Average picture size \sim 250 KB
- 3 1080P, H.265, 25 fps
- 4 SkyHawk Al surveillance drives are designed for always-on workloads of 550 TB/year. For higher transaction workloads, see Seagate's enterprise-class drive offerings.
- 5 Extended warranty options available. Consult your distributor for details.
- 6 Seagate does not recommend operating at sustained extreme temperatures. Operating at higher temperatures will reduce useful life of the product.

seagate.com

