

VTO6221E-P Apartment Outdoor Station



Technical Specification

Model	VTO6221E-P
System	
Main Processor	Embedded Micro Processor
Operation System	Embedded LINUX OS
Video	
Video Compression	H.264
Image Sensor	1/2.9" 2MP CMOS
Auto Gain Control	White Light
Lens	2 mm
Angle of View	H:140° V:82°
Day/Night	Color Image
Audio	
Audio Compression	G.711
Audio Input	Omnidirectional Mic
Audio Output	Built-in Speaker
Bidirectional Talk	Support Dual-way Bidirectional talk
Display	
Screen	2.3" OLED
Operation Mode	
Keypad	Mechanical Button with Braille
Reader	13.56 MHz

Features

- $\boldsymbol{\cdot}$ Small size apartment door station
- \cdot Supplemental lighting with white light
- · 2MP CMOS camera
- \cdot Mechanical button with Braille
- · Aluminium alloy plate, IP55, IK08
- \cdot Door release via password and Mifare card

Interface	
Alarm In/Out	1/1
Door Control	1 Relay Out 1 RS485 1 Feedback 1 Exit Button
Wiegand In	1
Storage	Micro SD Card, Max 64GB (reserved for software)
Network	
Ethernet	10 Mbps/100 Mbps
Network Protocol	TCP/IP
General	
Ingress Protection	IP55, IK08
Tamper Switch	1
Installation	Surface & Flush
Material	Aluminum
Power	12 VDC, 2 A, PoE (802.3af)
Power Consumption	Standby≤2 W, Working≤7 W
Working Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Relative Humidity	20%–95% (RH)
Dimensions	200 mm × 98 mm × 32mm (7.87" × 3.86" × 1.26")
Weight	1.5 kg (3.31 lb)

VTO6221E-P

Dimensions **View Area** 34.70 32.00 98.00 C ſ 0 0 H:140° 0.5m V. Ē \square 1.1 .2 .8 Α 200.00 °84 .5 1.6m 2 C .:0 : 0 8 ← 0.5m

Application



Rev 002.000 © 2023 Dahua. All rights reserved. Design and specifications are subject to change without notice. The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.